## www.selinc.com

C 3 4 5 -

## SEL-C345 EIA-232 Serial Cable

Male to Tinned Wires Cable for connecting a DTE device to a DTE device.

Part Number:

## Length<sup>(3)</sup>

Specify in feet with leading zeros (Example: 5 Feet = 005) Max length 100 Feet

<sup>(1)</sup> To verify your cable application, use the Cable Selector at <u>https://www.selinc.com/CableSelector/</u>.

 <sup>(2)</sup> Indoor Use Only, CM-Rated
<sup>(3)</sup> The performance of EIA-232 cable lengths greater than 50 feet cannot be guaranteed. As cable lengths increase, so does the risk of interference and equipment damage due to ground potential rise and induced voltages.

TERMI	NAĽ SERVEI	R		SEL (DTE)
9-PIN M/ "D" SUB DB-9-P	ALE CONNECTO	R		NO CONNECTOR (3) TIN WIRES 1/4" TRIM OUTER JACKET 3"
CABLE: 8 Conductor 22 AVVG 7/30 Tinned Copper with PVC Jacket (Shielded: Alpha 1298C or equal)				
	TX/RX+	2	ORANGE	
	TX/RX-	7	RED	
	GNĎ	5	BLACK	
	SHELL		SHIELD	NO CONNECTION

Making Electric Power Safer, More Reliable, and More Economical ®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA Phone: +1.509.332.1890 - Fax: +1.509.332.7990