DNV·GL

# KEMA TYPE TEST CERTIFICATE OF COMPLETE TYPE TESTS

Object	SDN switch		1069-17
Туре	SEL-2740S		
Rated input voltage Mechanical dass	125/250 Vdc 120/220/240 Vac 50/60 Hz 1	Ethernet ports Number of slots	20 6
			-
Manufacturer	Schweitzer Engineering Laborat Pullman, Washington, United St		
Client	Schweitzer Engineering Laborat Pullman, Washington, United St		
Tested by	DNV GL Netherlands B.V., Arnhem, the Netherlands		
Date of tests	14 February 2017 to 18 January	2018	

The object, constructed in accordance with the description, drawings and photographs incorporated in this Certificate, has been subjected to the series of proving tests in accordance with the complete type test requirements of

## IEC 61850-3:2013

The results are shown in the record of proving tests and the oscillograms attached hereto. The values obtained and the general performance are considered to comply with the above standard(s) and to justify the ratings assigned by the manufacturer as listed on page 7.

This Certificate applies only to the object tested. The responsibility for conformity of any object having the same type references as that tested rests with the Manufacturer.

\*) as declared by the manufacturer

This Certificate consists of 148 pages in total.

DNV GL Netherlands B.V.

J.P. Fonteijne Executive Vice President KEMA Laboratories



aboratories Arnhem, 20 March 2018

1

#### **INFORMATION SHEET**

#### KEMA Type Test Certificate

A KEMA Type Test Certificate contains a record of a series of (type) tests carried out in accordance with a recognized standard. The object tested has fulfilled the requirements of this standard and the relevant ratings assigned by the manufacturer are endorsed by DNV GL. In addition, the object's technical drawings have been verified and the condition of the object after the tests is assessed and recorded. The Certificate contains the essential drawings and a description of the object tested. A KEMA Type Test Certificate signifies that the object meets all the requirements of the named subclauses of the standard. It can be identified by gold-embossed lettering on the cover and a gold seal on its front sheet.

The Certificate is applicable to the object tested only. DNV GL is responsible for the validity and the contents of the Certificate. The responsibility for conformity of any object having the same type references as the one tested rests with the manufacturer.

Detailed rules on types of certification are given in DNV GL's Certification procedure applicable to KEMA Laboratories.

#### 2 KEMA Report of Performance

A KEMA Report of Performance is issued when an object has successfully completed and passed a subset (but not all) of test programmes in accordance with a recognized standard. In addition, the object's technical drawings have been verified and the condition of the object after the tests is assessed and recorded. The report is applicable to the object tested only. A KEMA Report of Performance signifies that the object meets the requirements of the named subclauses of the standard. It can be identified by silver-embossed lettering on the cover and a silver seal on its front sheet.

The sentence on the front sheet of a KEMA Report of Performance will state that the tests have been carried out in accordance with ...... The object has complied with the relevant requirements.

#### 3 KEMA Test Report

A KEMA Test Report is issued in all other cases. Reasons for issuing a KEMA Test Report could be:

- Tests were performed according to the client's instructions.
- Tests were performed only partially according to the standard.
- No technical drawings were submitted for verification and/or no assessment of the condition of the object after the tests was performed.
- The object failed one or more of the performed tests.

The KEMA Test Report can be identified by the grey-embossed lettering on the cover and grey seal on its front sheet.

In case the number of tests, the test procedure and the test parameters are based on a recognized standard and related to the ratings assigned by the manufacturer, the following sentence will appear on the front sheet. The tests have been carried out in accordance with the client's instructions. Test procedure and test parameters were based on ..... If the object does not pass the tests such behaviour will be mentioned on the front sheet. Verification of the drawings (if submitted) and assessment of the condition after the tests is only done on client's request.

When the tests, test procedure and/or test parameters are not in accordance with a recognized standard, the front sheet will state the tests have been carried out in accordance with client's instructions.

#### 4 Official and uncontrolled test documents

The official test documents of DNV GL are issued in bound form. Uncontrolled copies may be provided as a digital file for convenience of reproduction by the client. The copyright has to be respected at all times.

- 3 -

## **TABLE OF CONTENTS**

1	Summary	6
2	Identification of the object tested	7
2.1	Ratings/characteristics of the object tested	7
2.2	Description of the object tested	8
2.3	List of drawings	9
2.4	Photograph of test object	10
3	General information	11
3.1	The tests were witnessed by	11
3.2	The tests were carried out by	11
3.3	Reference to other reports	11
3.4	Subcontracting	11
3.5	Purpose of the tests	12
3.6	Measurement uncertainty	12
3.7	Instruments used	12
3.8	Standards	12
4	Test arrangement	13
5	Risk assessment	14
6	Marking and documentation	15
7	Packaging	16
8	Dimensions of structure	18
9	Functional performance requirements	19
10	Product safety	20
10.1	Inspection	20
10.1.1	Pre-inspection	20
10.1.2	Visual and functional inspection	20
10.2	Clearances and creepage distances	21
10.3	IP rating test	22
10.4	Impulse voltage test	23
10.5	Dielectric voltage test	25
10.6	Protective bonding resistance	27
10.7	Flammability of insulating materials, components and fire enclosures	29
10.8	Single-fault condition	31
11	Electromagnetic compatibility	32
11.1	Inspection	32

KEMA	Laboratories - 4 -	1069-17
11.1.1	Pre-inspection	32
11.1.2	Visual and functional inspection	32
11.2	Radiated emission	33
11.3	Conducted emission	38
11.4	Electrostatic discharge	44
11.4.1	Radiated interference	47
11.5	Electrical fast transient	49
11.6	Slow damped oscillatory wave	51
11.7	Surge	53
11.8	Conducted disturbance induced by radio-frequency fields	55
11.9	Power frequency magnetic field	57
11.10	Voltage dips and voltage interruptions on power supply voltage	59
11.11	Voltage ripple on DC power supply voltage	62
12	Energizing quantities	
12.1	Burden for DC power supply	64
12.2	Inrush current for DC	65
12.3	Burden for AC power supply	67
12.4	Inrush current for AC	68
13	Climatic environment	
13.1	Inspection	70
13.1.1	Pre-inspection	70
13.1.2	Visual and functional inspection	70
13.2	Photograph of test arrangement	71
13.3	Climatic environmental tests	72
13.3.1	Dry-heat test - operational	72
13.3.2	Cold test - operational	73
13.3.3	Dry-heat test at maximum storage temperature	74
13.3.4	Cold test at minimum storage temperature	75
13.3.5	Change of temperature test	76
13.3.6	Damp-heat steady-state test	77
13.3.7	Damp heat cyclic (12 h + 12 h) test	78
13.4	Measurement of insulation resistance	79
13.5	Dielectric voltage test	80
13.6	Protective bonding resistance test after damp-heat environmental test	81
14	Mechanical environmental condition tests	
14.1	Inspection	82
14.1.1	Pre-inspection	82
14.1.2	Visual and functional inspection	82
14.2	Photographs of test arrangement	83

KEMA	Laboratories - 5 -	1069-17
14.3	Vibration response test	86
14.4	Vibration endurance test	88
14.5	Shock response test	90
14.6	Shock withstand test	92
14.7	Bump test	94
14.8	Single axis sine sweep seismic test	96
15	Enclosure protection	
16	Photographs of printboards	
17	Measurement uncertainty	119
18	List of instruments used	
18.1	EMC equipment	120
18.2	Mechanical tests	121
18.3	Climate tests	121
18.4	Measurement equipment	121
18.5	Ethernet	121
19	Photographs of changes to the test object	
Append	x A Functional performance requirements	123

**KEMA** Laboratories

- 6 -

### **1 SUMMARY**

By order of the client type tests according to IEC 61850-3 have been performed on the test object.

Test / Measurement	Test result	
Dimensions of structure and visual inspection	Passed	
Functional requirements <sup>1</sup>	Passed	
Product safety	Passed	
Electromagnetic compatibility (EMC)	Passed	
Burden tests	Passed	
Climatic environmental conditions	Passed	
Mechanical environmental conditions	Passed	
Enclosure protection	Passed	

During the testing period the following changes were made to the test object:

The mounting brackets have been reinforced and extended. This change is required to pass the mechanical tests.

The changes to the test object have been documented in chapter 8 "Photographs of changes to the test object".