## Wiring Harness for Connectorized SEL-400G

Wiring Harness for Connectorized<sup>®</sup> SEL-400G Relays, Features CT Shorting Connector<sup>(1)</sup>. Wiring Harness Provides Connectors and Wiring for 18 AC Current Inputs and 6 AC Voltage Inputs.

Part Number:	W	Α	0	4	0	0	G				A
Wire Size for Current Inputs											
#10*								Α			
#12								В			
#14								С			
#16								D			
Wire Size for Voltage Inputs and Power											
#14									С		
#16									D		
#18									Е		
Wire Length											
4 Feet										1	
8 Feet										2	
12 Feet*										3	
16 Feet*										4	
20 Feet*										5	
Wire Type											
XLP (Wire Insulation: Crosslinked Polyethylene (XLP); Temp. Range: -40° to 90° C; Voltage Rating: 600 Volts)											Α

<sup>\*</sup> Additional Cost

- Wire Length: 6 inches
- Terminated with Banana Jacks
- No Wire Options

Making Electric Power Safer, More Reliable, and More Economical ®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA Phone: +1.509.332.1890 - Fax: +1.509.332.7990

 $<sup>^{(1)}\,</sup>$  To Order Test Harness, Specify Part Number WA0400G-0002