

SEL-2401

Satellite-Synchronized Clock^{(1),(2)}

Part Number:

2	4	0	1	0	X		X	
---	---	---	---	---	---	--	---	--

Firmware

Standard					0			
----------	--	--	--	--	---	--	--	--

Conformal Coat

None							X	
Conformally Coated Circuit Boards*							1	

Antenna

None								0
Low-Profile GPS Antenna (235-0209), 50 ohm, with 15 feet (4.5 m) of cable (C965-15)*								2
Complete Antenna Installation Kit: Includes GPS Antenna (SEL-9524A), 50 ft LMR-400 cable (SEL-C961-050), Gas Tube Coaxial Surge Protector and Mounting Kit (915900139), 25 ft LMR-400 cable (SEL-C961-025), Antenna Pipe-Mounting Kit (915900043)*								4

Accessories

GPS Signal-Acquisition Accessories		
SEL-C961 Low-Loss LMR 400, TNC Male to TNC Male Cable, 50 ohm*		Please see Online MOT or contact SEL REP or CSR for ordering information.
SEL-C965 RG-8X, TNC Male to TNC Male Cable, 50 ohm*		Please see Online MOT or contact SEL REP or CSR for ordering information.
Gas Tube Coaxial Surge Protector and Mounting Kit, Female TNC Connectors*	9 1 5 9 0 0 1 3 9	
GPS GNSS Antenna, Female TNC Connector, 50 ohm*	9 5 2 4 A	
Antenna Pipe Mounting Kit (for SEL-9524 GNSS Antenna)*	9 1 5 9 0 0 0 4 3	
Low-Profile GPS Antenna, 5 V, 33 dB Gain, Female TNC Connector*	2 3 5 - 0 2 0 9	
Antenna Surface Mounting Kit*	9 1 5 9 0 0 0 4 4	
Amplified 1X2 GPS Splitter*	2 4 0 - 0 1 0 9	
Time-Distribution Accessories		
SEL-C953 RG-58 Cable, BNC Connectors on Both Ends, 50 ohm*		Please see Online MOT or contact SEL REP or CSR for ordering information.
BNC terminator, 50 ohm*	2 4 0 - 1 8 0 0	
BNC Tee (Female/Female/Male, Equipment Mount)*	2 4 0 - 1 8 0 1	
BNC Tee (Female/Female/Female, In-Line Cable)*	2 4 0 - 1 8 0 2	
BNC Tee (Female/Male/Female, Equipment Mount)*	2 4 0 - 1 7 9 9	
SEL-C962 RG-58 Cable, BNC Connector to Tinned Wires, 50 ohm*		Please see Online MOT or contact SEL REP or CSR for ordering information.
SEL-C963 RG-58 Cable, Tinned Leads at Both Ends, 50 ohm*		Please see Online MOT or contact SEL REP or CSR for ordering information.
Wire-lead terminator, 50 ohm*	9 1 5 9 0 0 0 3 6	
Mounting Accessories		
DIN-Rail Mounting Kit (Included with Standard SEL-2401)*	9 1 5 9 0 0 0 1 5	

External Power Supply Accessories		
	Low-Voltage DC Power Supply, 125/250 Vdc or Vac Input*	9 3 2 1 6 0 X
	Low-Voltage DC Power Supply, 48/125 Vdc or Vac Input*	9 3 2 1 3 0 X
	15 Vdc Output; 100-240 Vac, 50-60 Hz Input*	2 4 0 - 0 0 5 6
	International Plug Adapter Kit (UK, EU, AUS) for 240-0056*	2 4 0 - 0 0 5 5

* Additional Cost

(1) Power supply input range: 9–30 Vdc

(2) Includes DIN-rail mounting kit.

Making Electric Power Safer, More Reliable, and More Economical®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA

Phone: +1.509.332.1890 - Fax: +1.509.332.7990