Wiring Harness for Connectorized SEL-300G

Features New Shorting Connector[1]

Part Number:	W	A	0	3	0	0	G	3	Y				A

Relay Configuration

Standard plus Synch-Check and Differential								3					

Wire Size for Current Inputs

#10*										A			
#12[2]										B			
#14										C			
#16										D			

Wire Size for Voltage Inputs and Power

#14[2]											C		
#16											D		
#18											E		

Wire Length

4 Feet												1	
8 Feet[2]												2	
12 Feet*												3	
16 Feet*												4	
20 Feet*												5	

Wire Type

XLP[2] (Wire Insulation: Crosslinked Polyethylene (XLP); Temp. Range: -40° to 90°C; Voltage Rating: 600 Volts)													A

[1] To order test harness, specify part number WA0300G3Y.
Wire Length: 6 inches
Terminated with banana jacks
No wire options

[2] Standard options. Specify part number WA0300G0YBC2A, WA0300G1YBC2A, WA0300G2YBC2A, or WA0300G3YBC2A.

Making Electric Power Safer, More Reliable, and More Economical ®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.
2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990

Copyright © SEL 2006-2019
All rights reserved.