

SEL-C808 Multimode Fiber-Optic Cable

62.5/125 Micron Core Diameter⁽¹⁾

Part Number:

C	8	0	8			0													
---	---	---	---	--	--	---	--	--	--	--	--	--	--	--	--	--	--	--	--

Cable Construction

Zipcord 1 Fiber ^{(2)*}					Z	0	1												
Zipcord 2 Fibers ^{(2)*}					Z	0	2												
Heavy-Duty Waterproof 2 Fibers ^{(2)*}					G	0	2												
Heavy-Duty Waterproof 4 Fibers ^{(2)*}					G	0	4												
Zipcord 1 Fiber (Plenum) ^{(3)*}					P	0	1												
Zipcord 2 Fibers (Plenum) ^{(3)*}					P	0	2												

Jacket Marking

Standard							0												
----------	--	--	--	--	--	--	---	--	--	--	--	--	--	--	--	--	--	--	--

Termination

Bulk Cable: No Terminations								0	0										
ST [®] Connector on Both Ends								S	S										
LC Connector to ST Connector								L	S										
LC Connector on Both Ends								L	L										
SC Connector on Both Ends								C	C										
SC Connector to ST Connector								C	S										
SC Connector to LC Connector								C	L										

Other Options

No Options																		X	
Pulling Loop (For use with Heavy Duty cables only)*																		1	

Length

Specify length Enter length in meters with leading zeros. (Example: 15 meters = 0015)																			
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Accessories

Field Termination Kit*	2	4	0	-	1	5	4	0
ST Connector*	2	4	0	-	1	5	4	1
LC Connector*	2	4	0	-	1	5	4	2
SC Connector*	2	4	0	-	1	4	9	7
ST Connector Splice Bushing*	0	9	0	-	5	0	1	2
SC Connector Splice Bushing *	2	4	0	-	1	8	1	1
LC Connector Splice Bushing*	2	4	0	-	1	8	1	0
Magnetic Cable Guide*	M	C	G					

*Additional Cost

⁽¹⁾ Cables are priced per options selected.

⁽²⁾ Riser (OFNR) rated cable, for use in riser and general purpose building applications.

⁽³⁾ Plenum (OFNP) rated cable, for use in plenum, riser and general purpose building applications.

Making Electric Power Safer, More Reliable, and More Economical®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990