

Management System Registered to ISO 9001/14001

Powertech Labs Inc.

12388 - 88th Avenue Tel: (604)590-7500 Surrey, British ColumbiaFax: (604)590-6611

Canada V3W 7R7

www.powertechlabs.com

Project: 17866-27

28 January 2008

Suneetha Parupalli G&W Electric Company 3500 West 127th Street Blue Island, IL 60406

Dear Suneetha:

Controller Simulated Surge Arrester Operation Test Report

Enclosed are three copies of the above test report:

If you have any questions or comments, you may reach me by phone at (604) 590-7464, by fax at (604) 597-6656, or by e-mail at bob.pollock@powertechlabs.com.

Yours truly,

Bob Pollock

Senior Technologist Power Engineering Labs

Encls.



Powertech Labs Inc.

12388 - 88th Avenue Surrey, British Columbia Canada V3W 7R7

Tel: (604)590-7500 Fax: (604)590-5347 www.powertech.bc.ca

CONTROLLER SIMULATED SURGE ARRESTER OPERATION TEST REPORT

Client:	G&W Electric Company, 3500 West 127th Street, Blue Island, IL 60406			
Test Date:	21 & 22 January 2008	Project:	17866-27	
Nameplate Data Controller: Manufacturer: Model: Part No.: Serial No.: Recloser: Manufacturer: Type/Model: Impulse level (BI Rated voltage: Rated current: Serial No.:	Schweitzer Engineering Labora SEL-351R 0351R21281X1XX224 2003078189 G&W Electric Company, Blu Viper VIP 398ER-12S	e Island, IL 604		
Test Witness:	Suneetha Parupalli, G&W Elect	tric Company		
Test Standard:	est Standard: IEEE Std C37.60-2003, Clause 6.13.2: "Simulated Surge Arrester Operation Test"			
Atmospheric Conditions:		Jan.21, 2008	Jan.22, 2008	
	Temperature Relative humidity Barometric pressure	17.6 °C 27% 764.2 mmHg	16.6 °C 26% 761.0 mmHg	
Test Current:	7 kA _{peak}			
Test Configurations (in accordance with the above standard):				
	B – surges applied to the source C – surges applied to the load b D – surges applied to a properly	A – surges applied to the source bushing with the recloser open B – surges applied to the source bushing with the recloser closed C – surges applied to the load bushing with the recloser closed D – surges applied to a properly rated transformer with the recloser open E – surges applied to a properly rated transformer with the recloser closed		
Test Results:	Operation Test performed in a	The controller and recloser operated normally following the Simulated Surge Arrester Operation Test performed in accordance with the test procedures as per the above standard. The controller complied with the requirements of IEEE Std C37.60-2003, Clause 6.13.2.		
Remarks:	Test configurations A, B & C pe	Test configurations A, B & C performed on Jan 21, D & E on Jan 22, 2008.		

Prepared by:

R.G. Pollock Senior Projects Specialist Approved by:

A.J. Vandermaar, P.Eng. 25 Jan C Manager, High Voltage Laboratory

This report shall not be reproduced except in full, without the written approval of Powertech Labs Inc.

Project #: 17866-27